HIGH SPEED SUPPORT VESSEI

AUSTAL HSSV 72



PRINCIPAL DIMENSIONS

Length Overall72.5 metresBeam (Moulded)18.2 metresBeam (Overall)18.66 metresDraft (Approx.)3.0 metresMaterialAluminium AlloyHull FormCatamaranMaximum Deadweight325 tonnes

MISSION/LOGISTICS/FLIGHT DECK

Deck Area 900 metres²
Clear Height 4.5 metres
Flight Deck 22.0 metres x 12.0 metres
Nominal Helicopter Capability NH-90

PERSONNEL DECK

Crew 69
Fixed Berths 69
Personnel Seating 260

PROPULSION

PERFORMANCE

Endurance 7 days
Max Speed (200T DWT) 35 knots
Range at 12.5 knots 2,150 nautical miles

WEAPONS AND SENSORS

Weapons 1 x 20mm naval gun
4 x 12.7mm GPMG
Sensors 1 x Electro Optical
Surveillance System (EOSS)
Operations Room 8 x Seated positions (15m²)

CAPACITIES

Vehicle Capacity158 lane metresBi-Folding Slewing Ramp12 x 4.25 metresBoat Launch Beam Crane System Max SWL12.0 tonnes





CLASSIFICATION

₱ 100 N5 RSA(200) HSDE NAVY TROOP CARRIER FO(HELIL)


₱ MC




HIGH SPEED SUPPORT VESSEL

AUSTAL HSSV 72


Vessel Type: High Speed Support Vessel



PROFILE




02 DECK



MAIN DECK

01 DECK



HULL

